



Split Pared
On/Off - **R410a**
Frio solo/Frio calor





Modo nocturno



Pantalla LED



Timer 24 horas



Defrost inteligente



Auto Limpieza



Auto Limpieza



Ahorro energético



Auto reinicio

R410A

Frío solo

MODEL			GWC12NB-D3NNA1A	GWC18NC-D3NNA1A	GWC24ND-D3NNA1A		
Capacidad	enfriamiento	btu/h	12,000	18,000	24,000		
EER/COP	W/W		2.61				
Alimentación	Ph - V - Hz		1Ph - 220/240V - 60Hz				
Entrada de poder	enfriamiento	W	1,235	1,800	1,950		
Corriente nominal	enfriamiento	A	7.0	12.42	15.85		
Carga	40'GP	sets	231	210	136		
	40'HQ	sets	269	244	156		
Volumen de aire	Evaporadora	m³/h(SH/H/ML)	550/460/380/280	650/620/575/530	850/780/650/550		
Evapor.	Nivel de presión de sonido	Evaporadora	dB(A)(SHH/ML)		37/35/32/-	49/45/41/37	45/42/39/35
	Dimensiones	ancho x alto x prof	mm		790x265x177	845x275x180	940x298x200
	Peso neto	Evaporadora	kg		9/10.5	10/13	13/17
Condensadora	Nivel de presión de sonido	Condensadora	dB		52	54	58
	Conexión Tubería	Gas	mm		Ø12		
		líquido	mm		Ø6		
	Dimensiones	ancho x alto x prof	mm		776x540x320	848x540x320	913x680x378
Peso neto	Condensadora	kg		30/32.5	41/46	46/50	

R410A

Frío/Calor

MODEL			GWH12AAB-D3NNA1A	GWH18AAD-D3NNA1A	GWH24AAE-D3NNA1A		
Capacidad	enfriamiento	btu/h	12,000	18,000	24,000		
	calefacción	btu/h	11,260	18,084	23,000		
SEER/HSPF	btu/ (h.w)		2.85/3		2.87/3.24		
Alimentación	Ph - V - Hz		1Ph - 208/230 - 60Hz				
Entrada de poder	enfriamiento	W	1,147	1,800	2,250		
	calefacción	W	1,130	1,767	2,100		
Corriente nominal	enfriamiento	A	7.29	10.9	13.96		
	calefacción	A	6.90	9.55	13.45		
Carga	40'GP	sets	240	186	136		
	40'HQ	sets	284	212	156		
Volumen de aire	Evaporadora	m³/h(SH/H/ML)	550/500/430/330	900/850/750/600	1200/1060/930/800		
Evapor.	Nivel de presión de sonido	Evaporadora	dB(A)(SHH/ML)		42/38/34/30	48/44/41/37	50/46/42/38
	Dimensiones	ancho x alto x prof	mm		773x250x180	970x300x225	1078x325x246
	Peso neto	Evaporadora	kg		8.5/9.5	13.5/16.5	16.5/19.5
Condensadora	Nivel de presión de sonido	Condensadora	dB		52	55	54
	Conexión Tubería	Gas	mm		Ø12-1/2"	Ø12-1/4"	Ø16 - 5/8"
		líquido	mm		Ø6-1/4"	Ø6-1/4"	Ø6-1/4"
	Dimensiones	ancho x alto x prof	mm		823x358x595	848x450x320	904x646x373
Peso neto	Condensadora	kg		28.5/31	82.7/88.2	110.25/116.9	

